

THE JENNISON-WRIGHT CO.

P.O. BOX 110591 CLEVELAND OHIO 44111-0591
(216) 671-5900 FAX (216) 671-1313
email: Sales@JennisonWright.com

FLOOR BLOCK CEMENT No. J-1201™

DESCRIPTION:

Floor Block Cement No. J-1201 is a heavy bodied high solids black adhesive especially adaptable for the setting or resetting of End Grain Wood Floor Blocks, Heavy-Duty Bituminous Asphalt Paving Blocks, Polymer Composite Jura-Blocks™.

Floor Block Cement No. J-1201 produces a superior adhesion of floor blocks to each other and to the base. It is nonflammable and easy to apply. No unpleasant odor. Area's of End Grain Wood Block over 500 square feet use "SUPER" Floor Block Cement No. J-1280.

APPLICATION:

No heating is required. Apply generously with a 1/4"x 1/4" notched trowel to a clean surface. Blocks are set in a staggered pattern firmly into place making sure the rows are straight and tight as possible. Excess material that seeps up through the cracks should be wiped or picked up from the blocks. End Grain Wood Block Floors must be sealed with Top-Kote™ Filler Sealer or Seal-(W)right® final finish systems soon after the wood blocks are set. This prevents excessive breakage and seals against oil and water absorption.

COVERAGE:

One gallon of Floor Block Cement No. J-1201 will adhere:

Wood Blocks : 25-35 square feet

All Other Blocks : 35-40 square feet

Packaged in 5 gallon containers.

CAUTION:

Contains asphalt emulsion. KEEP FROM FREEZING. Rotate Stock.
Consult Material Safety Data Sheet Prior To Using.

MISCELLANEOUS:

Also available are End Grain Wood Floor Blocks, Asphalt Paving Blocks, Polymer Composite Jur-Blocks, Steel Tile Anchor Floor Plates, Laminated "Pecan" Press Pit Floor Panel Sections, Preheat Solid Pitch, Floor Block Trench Fillers, Sealers and Special Coatings.

CAUTION: READ MATERIAL SAFETY DATA SHEET BEFORE USING ALL PRODUCTS. All statements and recommendations are based on experience we believe to be reliable. The use or application of these products being beyond the control of the seller or the manufacturer, neither the seller nor the manufacturer make any warranty expressed or implied, as to results or hazard from its use. The suitability, risk and liability of a product for any intended use shall be solely up to the user.