

# THE JENNISON-WRIGHT CO.

P.O. BOX 110591 CLEVELAND OHIO 44111-0591

(216) 671-5900 FAX (216) 671-1313

email: [Sales@JennisonWright.com](mailto:Sales@JennisonWright.com)

## WOOD BLOCK BINDER "PLUS 50"<sup>®</sup>

Wood Block Binder "PLUS 50" is a cold applied joint filler, binder and surface sealer that becomes an integral part of the wood and eliminates the need for Hot Pitch. "PLUS 50" should only be used on existing wood block floors that have open joints and/or loose block. "PLUS 50" when used periodically and as directed will extend the life of the wood block floor by binding the blocks together and prevent them from breaking up and having to replace the floor. "PLUS 50" also provides an excellent foundation for SEAL-(W)RIGHT<sup>®</sup> final finish systems and prevents dirt, debris and granular fillers migrating underneath the blocks.

### **APPLICATION:**

Wood Blocks must be fully acclimated prior to applying one flood coat of "PLUS 50" with a hard rubber squeegee. "PLUS 50" should be flowed over the surface and allowed to fill the joints while slowly pulling the squeegee with even pressure and removing the excess. A thin film left on the surface will turn black as "PLUS 50" is drying. NOTE: "PLUS 50" is not a final filler and to properly seal the surface of the wood block, it is necessary to apply SEAL-(W)RIGHT Finishes.

### **COVERAGE:**

Approximately 25 to 75 square feet per gallon depending on depth and width of cracks to be filled.

### **DRYING AND CURING:**

Depending upon temperature and drying conditions, two to four hours should be allowed for "PLUS 50" to turn black allowing foot traffic. At this time the final application of SEAL-(W)RIGHT may be applied. Allow at least 8-12 hours before placing floor in service.

### **CLEAN UP:**

Equipment should be cleaned immediately after use with soap and warm water.

### **CAUTION:**

Proper eye protection should be worn. Avoid skin and eye contact and use only with good ventilation. Keep from freezing. Consult Material Data Safety Sheet Prior To Use.

### **MISCELLANEOUS:**

Also available are End Grain Wood Floor Blocks, Polymer Wood Composite Jura-Block, Bituminous Asphalt Paving Blocks, Steel Tile Anchor Floor Plates, Laminated Pecan Trench/Pit Floor Panel Sections, Floor Block Trench Fillers, Sealers and Special Coatings.

**CAUTION: READ MATERIAL SAFETY DATA SHEET BEFORE USING ALL PRODUCTS.** All statements and recommendations are based on experience we believe to be reliable. The use or application of these products being beyond the control of the seller or the manufacturer, neither the seller nor the manufacturer make any warranty expressed or implied, as to results or hazard from its use. The suitability, risk and liability of a product for any intended use shall be solely up to the user.