

The Jennison-Wright Co.

P.O. BOX 110591 CLEVELAND OHIO 44111-0591
(216) 671-5900 FAX (216) 671-1313

LAMILITE®

FLOOR BLOCK ADHESIVE
(Protect From Freezing)

A light colored, mastic adhesive for installing The Jennison-Wright Co., Jenoil™ Treated End Grain Wood Block Floors and Composite Jura-Blocks™.

SURFACE PREPARATION:

Surface to be coated must be thoroughly cleaned, free of dirt, grease, moisture, coal tar, asphalt, and other contaminants. This is best accomplished by using a scurfing machine equipped with steel cutters. The thoroughly cleaned concrete slab should be primed by mopping with a saturated mop or sponge rubber squeegee using a solution of ½ Lamilite to ½ water. Leave no excess on the surface, and allow 30 to 60 minutes for drying. Mix solution well before applying.

APPLICATION:

Apply Lamilite as it comes from the container. Use a notched trowel with teeth not exceeding 3/16 inch and not less than 1/8 inch and work the Lamilite into the concrete with a swirling motion. The blocks must be installed within 30 minutes after the application of the Lamilite while it is still fresh. Follow standard procedures for laying blocks and drive up tightly. Single blocks can be replaced by dipping in the adhesive and resetting in the floor, using a sufficient amount to force the adhesive up into the surrounding block joints.

COVERAGE:

Approximately 35 square feet per gallon including primer.

DRYING AND CURING:

Allow 12-24 hours before placing the floor into service. The actual adhesive setting time is dependent upon the temperature and humidity. The floor may be sealed after adhesive is fully cured.

VENTILATION:

Adequate ventilation should be provided when using Lamilite adhesive. In the absence of adequate ventilation, approved respiratory protection, such as a respirator, should be worn.

CLEAN UP:

Equipment should be cleaned immediately after use with soap and water.

FIRST AID:

EYES: Immediately flush with clean water for at least 15 minutes. Call a physician.
INHALATION: If affected, remove to fresh air, administer oxygen and call a physician.
SKIN: Remove immediately with waterless hand cleaner and soap and water. Do not use solvents.
INGESTION: See physician immediately, show MSDS or label. DO NOT induce vomiting.
CONSULT MATERIAL SAFETY DATA SHEET.

MISCELLANEOUS:

Also available are End Grain Wood Floor Blocks, Asphalt Paving Blocks, Poly Block, Steel Tile Anchor Floor Plates, Laminated "Pecan" Press Pit Floor Panel Sections, Preheat Solid Pitch, Floor Block Trench Fillers, Sealers and Special Coatings.

NON-WARRANTY - The facts stated and the recommendations made for use of this product are based on our own tests and the test of others and are believed to be accurate. However, no guarantee of their accuracy is made. Purchasers should make their own test to determine the suitability of this product for their particular purpose. THIS PRODUCT IS SOLD WITHOUT WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, WITHOUT LIMITATION, IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. In no event shall The JENNISON-WRIGHT Co. be liable for direct, incidental or consequential damages.